

The CONSTABLE



CALIBER 5.56 x 45mm NATO (.223 REM)
ACTION Semi-auto, direct impingement
(Full-auto available to qualifying militaries/agencies)

UPPER MIL-SPEC upper receiver

WEIGHT 6.14lbs / 2.78kg (16" bbl empty)

BARREL 10.5" / 26.67cm
11.5" / 29.21cm
16" / 40.64cm

RIFLING 1:7, 1 / 2x28 barrel threads

LENGTH 32" / 81.28cm (16" bbl collapsed)

FINISH Black anodized

GAS BLOCK Midlength low profile gas block

HANDGUARD 14.5" M-LOK Renegade free-floating rail with four integrated QD sling mounts

MUZZLE DEVICE A2 flash hider

TRIGGER MIL-SPEC trigger

FURNITURE MIL-SPEC furniture

FIRE CONTROL MIL-SPEC P15 lower receiver
POF USA Ambi Selector Switch

MAINTENANCE Standard receiver/carrier group field strip procedures.

INCLUDES Nitride heat-treated bolt carrier group (includes cam pin)
6-position anti-tilt buffer tube
Mission First Tactical 30-round magazine

OPTIONS

Calibers: 5.56 NATO, .300BLK, 6.8SPC

Barrel Lengths: 10.5", 14.5", 16.5"

Picture and specs represent 16" barrel rifle.

